



Selection of products from price list with small pictures and short product description with important technical details.

Technical changes and errors reserved!

Content:	Тур	starting from page
Split bed Brake tester for light trucks 13 t	B 99 A	2
Split bed Brake tester for standard trucks 15 t	B 99 G	3
Compact Brake tester for standard trucks 15t Split bed Brake tester for heavy trucks 16 t	B 99 K B 110 G, B 101 M	6 8
Split bed Brake tester for heavy trucks 18 t	B 101 G	9
Compact Brake tester for heavy trucks 18 t	B 101 K	12
Split bed Brake tester for heavy trucks 18 t universal	B 100X-R18x	14
Split bed Brake tester for extreme heavy trucks 20 t	B 120	15
Accessories for truck brake tester	Universal	16
Software solutions	Universal	24
Side slip tester and Joint play detector	SP 110, GST 150	26

All test equipment are made under quality management system in accordance to ISO 9001:2008 Made by the German manufacturer SAXON Prüftechnik GmbH, Plauen.

From German Specialist for vehicle test equipment!

Product catalogue Split bed Brake tester B 99 A for light trucks up to 13t axle load



Order no:	Description		Picture of the product
25825 3	 B 99 A II Roller brake tester For light trucks or empty standard tru transporter and cars Scope of delivery: Installation chassis for installatio Split bed roller set with motors of Preparation for weight system Test width: Max. Test load (50%): Max. Axle load for drive over: Roller diameter: ECO Display with range Soft start – Automatic – Motors Test speed Automatic drive out assistant Remote control set 	n crossing a pit	
25825 2	B 99 A II Roller brake tester Scope of delivery like 25825 3, but: - Without installation chassis, for installation in a foundation made	de from cement.	

Product catalogue Split bed Brake tester B 99 G for standard trucks up to 15t axle load



21744 11	B 99 G Roller brake tester with large display	
	For standard trucks, trailer, bus, transporter and cars Scope of delivery: - Split bed roller set with motors underneath the rollers - Hot galvanized chassis and covers - Preparation for weight system - Test width: 800 x 2800 mm variable - Max. Test load (50%): 13 t - Max. Axle load for drive over: 15 t - Roller diameter: 234 mm - Large display with range 08 kN, 040 kN (opt. 0800, 04000 kgf) - Cupboard for electric and electronic - Soft start – Automatic – Motors 2x 11 kW - Test speed 2,5 km/h (optional 5,0 km/h) - Automatic drive out assistant - Remote control set	
21744 4	 B 99 G Roller brake tester with ATL display Scope of delivery like 21744 11, but: with ATL display and 22" LED monitor with Windows computer, keyboard and mouse with software SAXON diagnosis truck 	

Product catalogue Split bed Brake tester B 99 G for standard trucks up to 15t axle load



21744 12	 B 99 G Roller brake tester with Scope of delivery like 21744 11, but: with ECO display with range Electric and electronic system inside of ECO display 	h ECO display 08 kN, 040 kN (opt. 0800, 04000 kgf)	25 50 0 15 mm 1 1 25 50 0 15 mm 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
21991	 B 99 G Roller brake tester with Scope of delivery like 21744 11, but: with compact display with range Electric and electronic system inside of ECO display VOSA Approval for UK 	h Compact display 08 kN, 040 kN (opt. 0800, 04000 kgf)		

Product catalogue Split bed Brake tester B 99 G for standard trucks up to 15t axle load



22029 12	 B 99 G-F Roller brake tester with ECO display For standard trucks, trailer, bus, transporter and cars and specially made for small foundations Scope of delivery like 21744 12, but: Reduced chassis dimensions and reduced deepness. used for replacements. Test width: 800mm – 2800 mm (variable) 	
22029 17	 B 99 G-F-I Roller brake tester with ECO display For standard trucks, trailer, bus, transporter and cars and specially for agricultural tractor Scope of delivery like 21744 12, but: Inner bearings of the rollers inside of the rollers means, pit can be used in full width Test width: 800mm – 3100 mm (variable) 	

Product catalogue Compact Brake tester B 99 K for standard trucks up to 15t axle load



21743	B 99 K Roller brake tester with large display	
	For standard trucks, trailer, bus, transporter and cars	15 15 15 15 15 15 15 15 15 15 15 15 15 1
	Scope of delivery:	
	 Compact bed roller set with motors underneath the rollers Hot galvanized chassis and covers Preparation for weight system Test width: 800 x 2800 mm Max. Test load (50%): 13 t., Max. Axle load for drive over: 15 t. Roller diameter: 234 mm Large display with range 08 kN, 040 kN (opt. 0800, 04000 kgf) Cupboard for electric and electronic Soft start – Automatic – Motors 2x 11 kW Test speed 2,5 km/h (optional 5,0 km/h) Automatic drive out assistant Remote control set 	
21743 4	 B 99 K Roller brake tester with ATL display Scope of delivery like 21743, but: with ATL display and 22" LED monitor with Windows computer, keyboard and mouse with software SAXON diagnosis truck 	



21743 3	B 99 K Roller brake tester with ECO display Scope of delivery like 21743, but: • with ECO display with range 08 kN, 040 kN (opt. 0800, 04000 kgf) • Electric and electronic system inside of ECO display	$\begin{array}{c} 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 $

Product catalogue Split bed Brake tester B 110 G / B 101 M for heavy trucks up to 16t axle load



25113 4	B 110 G Roller brake tester with large display	
	For standard trucks, trailer, bus, transporter and cars Special flat construction for in ground installation. Inner bearings of the rollers inside of the rollers for full pit width	$\begin{array}{c} 20 \\ 15 \\ 10 \\ 10 \\ 10 \\ 10 \\ 10 \\ 10 \\ 1$
	Scope of delivery:	eren and a second
	 Split bed roller set with motors outside of the rollers Hot galvanized chassis and covers Preparation for weight system Test width: 800 x 3000 mm variable Max. Test load (50%): 13 t., Max. Axle load for drive over: 16 t. Roller diameter: 234 mm Large display with range 8 kN, 040 kN (opt. 0800, 04000 kgf) Cupboard for electric and electronic Soft start – Automatic – Motors 2x 11 kW Test speed 2,5 km/h (optional 5,0 km/h) Automatic drive out assistant 	
25113 15	B 110 G Roller brake tester with ATL display	
	Scope of delivery like 25113 4, but:	
	 with ATL display and 22" LED monitor with Windows computer, keyboard and mouse with software SAXON diagnosis truck 	

Product catalogue Split bed Brake tester B 110 G / B 101 M for heavy trucks up to 16t axle load





Product catalogue Split bed Brake tester B 101 G for heavy trucks up to 18t axle load



21746 6	B 101 G Roller brake tester with large display For heavy trucks, trailer, bus, transporter and cars Scope of delivery: - Split bed roller set with motors underneath the rollers - Hot galvanized chassis and covers - Preparation for weight system - Test width: 800 x 2800 mm variable - Max. Test load (50%): 16 t (with optional 15kW) - Max. Axle load for drive over: 18 t. - Roller diameter: 234 mm - Large display with range 010 kN, 050 kN - Cupboard for electric and electronic 2x 11 kW (optional 15 kW) - Test speed 2,5 km/h (optional 5,0 km/h) - Automatic drive out assistant Remote control set	
21746 3	 B 101 G Roller brake tester with ATL display Scope of delivery like 22746 6, but: with ATL display and 22" LED monitor with Windows computer, keyboard and mouse with software SAXON diagnosis truck 	



21971 3	B 101 G Roller brake tester	with ECO display	
	Scope of delivery like 21746 6, but: - with ECO display with range	010 kN, 050 kN For UK 0800, 04000 kgf	$\begin{array}{c} 15 \\ 10 \\ 10 \\ 10 \\ 10 \\ 10 \\ 10 \\ 10 \\$
	 Electric and electronic system inside of ECO display 		Diff. [%] pm [bar] Pd (dat)]
			Like in the picture but 50 kN value on pointers!

Product catalogue Compact Brake tester B 101 K for heavy trucks up to 18t axle load



21745	B 101 K Roller brake tester with large display		
	 For heavy trucks, trailer, bus, transporter and cars Scope of delivery: Compact bed roller set with motors underneath the rollers Hot galvanized chassis and covers 	20 25 30 34 07 20 25 30 15 33 31 32 35 35 10 = 1 5 0 5 5 0 5 0 50 10 = 1 5 0 5 0 5 0 50 10 = 1 10 = 1	
	 Preparation for weight system Test width: 800 x 2800 mm Max. Test load (50%): 16 t (with optional 15kW) Max. Axle load for drive over: 18 t. Roller diameter: 234 mm Large display with range 010 kN, 050 kN For UK 0800, 04000 kgf Cupboard for electric and electronic Soft start – Automatic – Motors 2x 11 kW (optional 15kW) Test speed 2,5 km/h (optional 5,0 km/h) Automatic drive out assistant Remote control set 		
21745 5	B 101 K Roller brake tester with ATL display Scope of delivery like 21745, but: • with ATL display and 22" LED monitor • with Windows computer, keyboard and mouse • with software SAXON diagnosis truck		

Product catalogue Compact Brake tester B 101 K for heavy trucks up to 18t axle load



18432 3	 B 101 K Roller brake tester Scope of delivery like 21745, but: with ECO display with range Electric and electronic system inside of ECO display 	with ECO display 010 kN, 050 kN For UK 0800, 04000 kgf	C 15 10 10 10 10 10 10 10 10 10 10	
			Like in the picture but 50 kN val	ue on pointers!

Product catalogue Split bed Roller brake tester B 100X-R18X for heavy trucks up to 18t axle load



20667	B 100-R18u Roller brake tester with large display Combined brake tester for heavy trucks, trailer, bus, transporter and cars with very small wheels by rollers with adjustable distance and axle lift. Scope of delivery: - Split bed roller set with motors out side - Set of installation chassis flat design - Hot galvanized roller beds and installation chassis - cupboard with electronic - Roller distance shifting for cars and trucks, pneumatical driven - Test width: 800 x 2800 mm - Roller distance: near/far 400 mm / 500 mm - Large pointer display with range 08 kN, 040 kN - Soft start – Automatic – Motor drive 2x 11kW - Pneumatic lift bar capacity: 18 t - Automatic drive-out assistance -	
27442	B 100B-R18u Roller brake tester with large display Combined brake tester for heavy trucks, trailer, bus, transporter and cars with very small wheels by rollers with adjustable distance. Scope of delivery: - Split bed roller set with motors out side - Hot galvanized roller beds and installation chassis - cupboard with electronic - Roller distance shifting for cars and trucks, hydraulically driven - Test width: - 800 x 2800 mm - Roller distance: near/far - Moor miller display with range - Soft start – Automatic – Motor drive - Soft start – Automatic – Motor drive - Remote control set	<image/>

Product catalogue Split bed Roller brake tester B120 for extreme heavy trucks and crane up to 20t axle load







Order no:	Description	Picture of the product
21251	Remote control set - Receiver with lens for range extension up to 30 m - IR - Hand set with different front sticker versions - Cable set for installation	
15626	Second test speed 11kW Motors with 2 speed for 2,6 km/h and 5,2 km/h	
21760 4	4WD extension with automatic 4WD detectionFor brake testers with 11kWwith automatic detectionwith reverse test directionOptional also for all other motor power	4x4, 6x6, 8x8
27451	4WD Synchronization truck 400V/11kW high quality synchronisation with frequency inverter	
15623	Brakes for rollers Motors with electromagnetic brake	
26565	Tractor extension - Single wheel brake (requires 15626) Special side per site control for brakes for testing vehicles with big tires as on agricultural machines	



20749 4	Sensors for measuring way distance	
201494	In digital tachometer	
20741	Pedal effort meter (with cable 25 m) Measuring range: 1000 N	
22558 1	Pedal force sensor, radio control Measuring range: 1000 N	
25954	Ext. Belt for hand brake test used with part-no. 21817 + 22558 1	
20523	LCD Display 1x5 character – Multifunction -	
20522	LCD Display 4x2 character – Efficiency, difference, pit safety	
20524	LCD Display 2x5 character – Dynamic wheel load	



20758	SP 110 Side slip tester integratedUsing LCD display and electronic of brake testerMax. Wheel load:10 t (one wheel)Measuring range:+/- 16 mm/m (m/km)Cable set:15 mDimensions (LxWxH):1000 mm x 800 mm x 73 mm	
23420	Installation frame SP 110 integrated	
11163 2	Work pit safety device (3-beams)	-7
11164 1	Work pit safety device (4-beams)	
26993	Manual swivel arm for work pit safety device	
27007	Automatic swivel arm for work pit safety device Pneumatic driven	



26453 1	Slip measurement for truck brake tester	
28223	Brake rollers with welded steel surface for tires with spikes	
20735 1	Air pressure sensor-set hoses with box	
	 2 Air pressure sensors 20 bar mounted in a box for wall installation in the pit, 15m cable 2 Rubber hoses 15m with ISO adaptor 	
25160 2	 Air pressure sensor radio system G9V2 1Pm/1Pz 2 Transmitter for air pressure 0-20 bar with hose and ISO adaptor Receiver unit with Interface to brake tester Compact charging station for max 5 transmitters Optional Alarm unit 	
25161	Add. air pressure sensor for G9V2	
25161 44	Hydraulic sensor for radio system	



19608	Alarm device for radio system	
15660	Pedestal for ECO display	SAXON°
15660/2	Pedestal for Large display Turning version	



15661/1	Swivelling wall bracket Large display	
26772	Wall bracket 1 turning axle	
19458/1 15658/1	Dynamic weight system 8 points Dynamic weight system 4 points	
17880	NSP 150/U Load simulator - pneumatic Pneumatic load simulator Max additional load: 12.000 kg Tightening way: 200 mm Air pressure: 6 bar	



26934	HV 200 Lifting device B 99G / B 101GHydraulic lifting for split bed brake roller setMax. lifting capacity:16.000kgLifting way:200 mm (optional 300 mm)	
26934 5	HV 200 Lifting device B 99K / B 101K Hydraulic lifting for compact brake roller set	
	Max. lifting capacity:8.000kgLifting way:200 mm (optional 300 mm)	
27601	Tablet-Computer 10" with protection case	
	Different models, as available on market	26 % 14697 kg 26 % 99 P 2 100 100 100 100
22584	Diagnosis and virtual remote control software for tablet computer	
	 Diagnosis software for touch screens with big on screen touch button row 	Par 1,9 18829 N 0 % 18798 N Pd 89 7440 kg 7257 kg Ph 0 Maximum VPL / forwarden to Max
26444 1	Tablet-Computer 8"	
	Different models, as available on market	
	Tablet computer with WINDOWS operation system required!	P 2 H-1 1 Pm 0 Pm 0



16985	Computer Terminal		
	Dimensions:		
	Height:	1.720 mm with rollers	RITE INTO
	neight.	1.600 mm without rollers	
	Width:	680 mm	
		600 mm	
	Depth:	600 mm	
	Delivery with 4 rolle	rs (2 with brake) by standard.	
	All access is from fro		8
	The doors are all loc	kable with same key (6 keys in delivery).	···/0 N ⁹
		tors of 22" and space also for computer.	SAXON®
		ent big for keyboard and mouse and with	
	high quality rolling g	uideways.	
	The bottom section	is with double door 180° flapping.	•
	Shelf height adjustal	ble i.e. for computer or printer.	
	The cabinet is with v	entilation grills.	
	Outlet for power sup	oply from rear side. Cable rails inside.	
	Color is SAXON blue	and with SAXON Logo in white.	
	(Replacing old PC T	erminal 21618 since 2016)	
24430	High performance	wireless access point	
	For tablet computers	and smart phone	
		isplay and remote control	wireless
		are on main computer	



22582 2	 SAXON Datacenter + Diagnosis software for truck tester Full version - Order processing system Data base system for truck brake tester. With client-, vehicle-, inspector- and order database. Advanced graphic evaluations for truck brake testing with advanced printing function. Diagnosis software for indication of brake values Special VI Database data base extension for UK with DTP Number support for truck, bus coach and trailers and special test report. Sample brake master files as available including. 	
22597	SAXON Diagnosis Software for truck tester - Small version - Software for indication of brake test values during brake test Indication of brake force, difference, weight, ovality, air pressure, pedal force with graphic and digital indications Simple function for client and vehicle data Basic printing function for simple test reports	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$



26964	Virtual remote control extension	SAXON Remote Control +
	Extension for SAXON diagnosis software	
	as "on screen" remote control	
	and as browser site for use on smart phone	
	·	
		• • • • • • • • • •
		Saxon
28884	Portrait display extension	
		ENB112 VIN: 171323 Insp: 294
	Software as large display for brake testers	Manual Mode
	- Large analogue display for brake force – dynamic scaling	
	- Digital display for brake force kN or kgf, difference %, weight kg	P2 20 12 Pz1
	- Digital display of air pressure bar, pedal force in N, efficiency %	kN ¹⁵ ²⁵
	- Indication for brake system and axle number	
	- Indicators for reverse direction, 4x4 mode, axle in position	
	 Slip symbols, difference symbol, direction of rotation Reflection of remote control commands 	
	- Symbols for safety device, load simulator and lifting device	5 (D) 2
	Requires monitor or TV screen with full HD resolution mounted	
	in portrait position as in the picture.	20,64 ^{kn} △32% 13,98 ^{kn}
	Monitor 40" - 60" recommended.	
	IPS Panel recommended (for large display angle). Computer with HDMI interface is need	Pm 0,0 bar 62 % Pz1 0,0 bar
		11142 kg % Pd 0 N

Product catalogue Tachometer / Speed tester



21752	SP 110 Side slip tester with digital display Scope of delivery: Installation frame for light barrier Side slip plate and light barrier Digital display unit with LCD Measuring range: +/- 16 mm/m Max wheel load: 10.000 kg Cable set pre wired 15 m	<image/>
20702 16	GST 150 Joint play detector LED MP EW-G Scope of supply: - 2 pieces galvanized chassis - Max. axle load: 18.000 kg - Moving directions: 8 + 1 - Moving way in all directions: 100 mm - Moving force: 20 kN (opt. 30kN) - Moving speed: 3 cm/s (opt. 5cm/s) - Hydraulic pump: 2,2 kW (opt. 3kW) - 2 pieces installation frames closed for pit jack crossing - Hydraulic aggregate and electronic control installed on a mounting plate - Hand lamp with triple LED spot light, 5 rocker switches, - 12 m cable exchangeable - Automatic test program - Centring in middle position by automatic test program	<image/>

Product catalogue Tachometer / Speed tester



20702 17	GST 150 Joint play detector LED EX EW-GScope of supply:2 pieces galvanized chassis- 2 pieces galvanized chassis- Max. axle load:18.000 kg- Moving directions:8 + 1- Moving way in all directions:100 mm- Moving force:20 kN (opt. 30kN)- Moving speed:3 cm/s (opt. 5cm/s)- Hydraulic pump:2,2 kW (opt. 3kW)- 2 pieces installation frames closed for pit jack crossing- Hydraulic aggregate and electronic controlinstalled in a closed cupboard- Hand lamp with triple LED spot light, 5 rocker switches,- 12 m cable exchangeable- Automatic test program- Centring in middle position by automatic test program	
25250 1	Extra charge for hand lamp - Ultra brightly For use in day light conditions and direct sun	
26875	Control system with radio transmission For Joint play detectors. - LED spot light with rubber protector and belt clip - Charger station - Power supply - Special controller board - Radio antenna for wireless connection	